

GAF

# EVERGUARD® TPO



## Description

EverGuard® TPO Quick Spray Adhesive and EverGuard® TPO Quick Spray Adhesive LV50 are sprayable, solvent-based contact adhesives useful for bonding smooth EverGuard® and EverGuard Extreme® TPO membranes to various substrates.

## Features and Benefits

- Up to 10 squares (93 square meters) of installed membrane per canister
- Faster installation than traditional bonding adhesive
- High initial tack

## Application:

- Substrate should be dry, clean, and free from oil, grease, and other contaminants
- Spraying from 8"–12" (203 – 305 mm) away, apply adhesive uniformly to both the substrate and the underside of the membrane
- Allow adhesive to dry to a tacky feel before bonding membrane to substrate
- Apply at an ambient temperature of 20°F (-6.7°C) and above. The cylinders must be kept above 50°F (10°C) for the product to spray properly. Utilize power-heated blankets and hot boxes when necessary. Ensure that cylinder temperatures stay below 150°F (65.6°C)
- Apply pressure with a push broom or weighted roller to ensure complete bonding

# EverGuard® TPO Quick Spray Adhesive

## EverGuard® TPO Quick Spray Adhesive

Item Number: 7792

VOC: 489 g/L

Shelf Life: 1 year

Installation Temperature: 20°F (-6.7°C) and rising

Canister Weight: 40.15 lb. (18.2 kg)

Adhesive Weight: 30 lb. (13.6 kg)

Cleaner SKU: 7802

Hose & Gun SKU: 7804

## EverGuard® TPO Quick Spray Adhesive LV50

Item Number: 7801

VOC: <80 g/L

Shelf Life: 1 year

Installation Temperature: 20°F (-6.7°C) and rising

Canister Weight: 36.3 lb. (16.5 kg)

Adhesive Weight: 27 lb. (12.25 kg)

Cleaner SKU: 7803

Hose & Gun SKU: 7804

*\*Coverage rates and flash time may vary in colder temperatures.*

TPO Adhesive

We protect what matters most™

[gaf.com](http://gaf.com)



Refer to UL Online Certification Directory for actual assemblies.