

Description:

Help prepare TPO for heat-welding by cleaning exposed or contaminated seams, removing any residual soap or other cleaners, and revitalizing aged or weathered membranes. Available in 1 gallon cans or 15 oz Aerosol, which is ideal for repair and maintenance applications

Application:

Minimal contamination: Membrane that has been exposed overnight or for only a few days to airborne debris, foot traffic, dew, or light precipitation can usually be cleaned with a white cloth moistened with EverGuard® TPO Seam Cleaner. Be sure to wait for the cleaner to properly dry or flash off before welding.

Dirt contamination: Membrane that is dirt-encrusted should first be cleaned with a mildly abrasive scrubbing pad and a non-abrasive, non-bleach, low-residue cleaner. After the dirt has been removed, the membrane must be cleaned with a white cloth moistened with EverGuard® TPO Seam Cleaner. Be sure to wait for the cleaner to properly dry or flash off before welding.

Weathering: Membrane that is weathered or oxidized should first be cleaned with a mildly abrasive scrubbing pad and EverGuard® TPO Cleaner. After the weathered or oxidized top layer is removed, the membrane must be cleaned with a white cloth moistened with EverGuard® TPO Seam Cleaner. Be sure to wait for the cleaner to properly dry or flash off before welding. Note: The same procedure may be needed for unexposed membrane left in inventory for a year or longer.

Bag fresh: Do not use EverGuard® TPO Seam Cleaner on recently opened or "bag fresh" material that has been exposed for less than 12 hours, unless that material has been otherwise contaminated.

Specifications		
Can size	1 gal.	15 oz. Aerosol
Cans per carton	4	12
Weight per case	33 lb. (14.96 kg)	N/A
Cases per pallet	48	N/A
Product SKU	7793	7793A



Storage Notes:

Apply EverGuard® TPO Seam Cleaner where the ambient temperature is 40°F (4°C) and rising. Store in a clean and well-ventilated area where the ambient temperature is 40°F (4°C) – 90°F (32.2°C). Do not allow to freeze. The cleaner shelf life is 12 months from date of manufacture when properly stored. The VOC content is 861 grams/liter.



Visit gaf.com



GAI