

## Multi-Purpose Adhesive Sealant



### Adheres To


- Vinyl
- Brick
- Fiberglass
- Aluminum
- RV
- Concrete
- Masonry
- Wood
- Stone
- Marine
- Fiber Cement
- Steel
- Ceramics
- Building Paper
- Single-Ply

### Product Advantages


- Waterproof, Premium All-Weather Silicone
- Excellent Tooling Characteristics
- Service Temperature -40 F to +400 F
- Application Temperature -20 F to +120 F
- UV and Mildew Resistant
- Permanently Flexible
- Will Not Shrink, Crack, Sag or Slump
- Weather Tight Seal
- Low Odor
- Solvent Free
- Invisible to UV Light
- Easily Gunned at all Temperatures




White  
M100



Blue White  
M101



Antique White  
M105



Canvas  
M107



Black  
M110



Gray  
M111



Dark Bronze  
M120



Lincoln Bronze  
M121



Imperial Brown  
M130



Earthtone  
M132



Terratone  
M134



Dark Sand  
M138



Beige  
M140



Tan  
M141



Almond  
M143



Sandstone  
M146



Translucent  
M150



Forest Green  
M162

### Product Information

- Description - Multi-Purpose Adhesive Sealant
- Item Number - 02-MX0XXXX-10C1
- Size - 10.3 FL. OZ (304 mL)
- Unit Dimensions - 9" X 2" X 2"

Also available in sausage packages:

Item Number - 02-MX0XXXX-20S1

Size - 20 FL Oz

Dimensions - 12 3/4" x 2" (unit)

13 1/2" x 8 1/4" x 6" (case)

### Case Pack Information

- Description - Multi-Purpose Adhesive Sealant
- Item Number - 02-MX0XXXX-10C1
- Dimensions - 11 15/16" X 9 15/16" X 8 1/8"
- Case Weight - 10 lbs - 12 packs  
20 lbs - 24 packs
- Cases Per Pallet - 60 - 24 packs  
120 - 12 packs

**Over 60 colors available for siding, fiber cement, roofing gutters, coil & trim**

## Multi-Purpose Adhesive Sealant

### Technical Information

Product: Novaflex Multi-Purpose Sealant  
 Appearance: Smooth paste  
 Application Temperature: -20 °F to +120°F (-28°C to 50°C)  
 Service Temperature: -40°F to +400°F (-40°C to 200°C)  
 Adhesion: Excellent to most common building materials  
 Consistency: Non-sag  
 Bridging Ability: Excellent, bridges gaps to 3/4" (2 cm)  
 Gunning Extrusion: Very easy to gun and clean up  
 Durability: +/- 35/50% joint movement depending on color/formulation  
 Flexibility: Remains flexible to -40°F  
 Water Resistance: Excellent  
 – Not to be submerged  
 Exterior Weathering: Excellent

Aging: Excellent  
 Freeze-Thaw Stable: Will Not Freeze  
 Odor: None

Skin Time:

- 40°F/40% relative humidity – 40 minutes
- 75°F/50% relative humidity – 10 minutes
- 95°F/95% relative humidity – 5 minutes

Through and Cure Time:

- 40°F/60% relative humidity – 2-3 days
- 75°F/50% relative humidity – < 24 hrs

Weight per gallon: 10.2 pounds  
 Solids: 97%  
 Flash Point: > 400°F

Novaflex® Multi-Purpose Adhesive Sealant is a premium all-weather medium modulus silicone that stays flexible and resistant to cracking and discoloration. Cured sealant resists mildew. This premium all-weather silicone is tack free in 10 minutes and is completely cured in up to 2 days. Cure time is with above 30% relative humidity and varies with temperature and humidity.

### Product Specs

Coverage: 28 linear ft. using a 1/4" bead or 14 linear ft. using a 3/8" bead.

Specifications: Meets or exceeds the performance characteristics of: ASTM C-920, AAMA 802.3, 805.2, 808.3, TT-S-001543A and TT-S-230C.

Shelf life: Use product within 18 months from manufacturers date. FREEZE THAW STABLE. Store product at 40°F to 80°F.

MAX VOC: less than 34 g/l (<4% by weight). VOC compliant in all 50 states.

### Recommended For Sealing

- Windows
- Doors
- Metal Roofs
- Head Expanders
- Door Sills
- Flashing
- Cap Beading
- Reglazing Broken/Defective Glass
- Gutters
- Nail Fins
- Fiber Cement
- Vinyl Siding
- Trim Coil

### Not Recommended For

- Joints continuously submerged under water
- Areas needing paint or stain
- Spaces confined from atmospheric moisture during cure
- On surfaces that might bleed oils, plasticizers or solvents
- In structural glazing applications
- Painted Applications

Limited Warranty: Satisfaction guaranteed when handled and applied according to label instructions. Call 1-800-380-0138 for Customer Service.

**CAUTION!** Methyl ethyl ketoxime, methyl and thyl alcohol released during cure. Avoid breathing vapors. Avoid prolonged or repeated skin contact.

### KEEP OUT OF REACH OF CHILDREN

First Aid: Skin: Wash with soap and water. Eyes: SEEK IMMEDIATE MEDICAL ATTENTION. Inhalation causing discomfort: Remove to fresh air. If discomfort persists or any breathing difficulty occurs, or if swallowed, SEEK IMMEDIATE MEDICAL ATTENTION. Additional information please refer to MSDS.

Disposal: For disposal of material follow federal, state and local regulations.



**NOVAGARD**  
 Solutions™  
 Engineered Products... Innovative Thinking

5109 Hamilton Ave.  
 Cleveland, OH 44114  
 1-800-380-0138  
 www.novagard.com  
 Made in USA. For commercial use.